NSN 5305-01-369-5511

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-369-5511 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.203 inches **Fastener Length:** Between 0.587 inches and 0.607 inches **Head Style:** Flat countersunk **Head Diameter:** 0.317 inches **Internal Drive Style:** Cross recess type 1 **Material Accommodated Thickness:** Between 0.075 inches and 0.089 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 locking featuresteel comp 304 stand-off **Material Specification:** Ams5737 assn standard single material response locking featuremil-s-23195 military specification single material response stand-off **Surface Treatment:** Passivate locking featurepassivate stand-off **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response locking featureqq-p-35 federal specification single treatment response stand-off **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

Fiig:

A003b0

NSN 5305-01-369-5511

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-23195 spec.