## NSN 5305-01-369-5586

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-369-5586 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Locking Feature:** Patch or strip or pellet **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Locking Feature Material:** Plastic polyamide **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas1190 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-369-5586

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0