NSN 5305-01-369-7231

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-369-7231 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.362 inches **Fastener Length:** Between 0.987 inches and 1.027 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.491 inches and 0.507 inches **Shoulder Diameter:** 0.246 inches first shoulder and 0.249 inches first shoulder **Shoulder Length:** 0.635 inches first shoulder and 0.655 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Aluminum alloy **Material Specification:** Mil-s-7839 alloy military specification 1st material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 federal specification all treatment responses **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1299 professional/industrial association standard Shelf Life: N/a

. .

Unit Of Measure:

NSN 5305-01-369-7231

Shoulder Screw - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7839 spec.