

View Online at <https://aerobasegroup.com/nsn/5305-01-369-7249>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.804 inches and 0.875 inches

Fastener Length:

Between 0.860 inches and 0.890 inches

Head Style:

Pan

Head Diameter:

Between 0.477 inches and 0.492 inches

Head Height:

Between 0.140 inches and 0.150 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Product Name:

Navy special project

Screw Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Locking Feature Material:

Plastic polyamide

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.