NSN 5305-01-369-8886

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-369-8886 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.298 inches and 0.313 inches **Fastener Length:** 2.250 inches **Head Style:** Knurled no. 5 **Head Diameter:** Between 0.505 inches and 0.515 inches **Head Height:** Between 0.547 inches and 0.577 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.740 inches and 1.760 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 or steel comp 303 plus x or steel comp 303ma or steel comp 303pb or steel comp 303se or steel comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 430fse or steel comp 420f or steel comp 420fse or steel comp 440f **Material Specification:** Astm a581 assn standard all material responses or astm a582 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-01-369-8886

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.