NSN 5305-01-369-9502



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-369-9502 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.219 inches and 0.281 inches **Fastener Length:** Between 0.843 inches and 0.909 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.344 inches and 0.406 inches **Head Height:** Between 0.156 inches and 0.239 inches **Shoulder Diameter:** 0.248 inches first shoulder and 0.250 inches first shoulder **Shoulder Length:** 0.625 inches first shoulder and 0.628 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Astm a582 cond. A assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 1 federal specification single treatment response **Thread Series Designator:**

Unf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5305-01-369-9502

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-21472 spec.