## NSN 5305-01-369-9735

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-369-9735

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.284 inches and 0.393 inches
Fastener Length:
Between 0.346 inches and 0.393 inches
Head Style:
Hexagon
Head Height:
Between 0.105 inches and 0.120 inches
Width Between Flats:
Between 0.305 inches and 0.314 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Screw Material Specification:
Mil-c-13924 military specification single material response
Screw Surface Treatment:
Oxide
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
63.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unc
Specification Data:
80205-nas1802 professional/industrial association standard
Shelf Life:

N/a

## NSN 5305-01-369-9735

Machine Screw - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.