

View Online at <https://aerobasegroup.com/nsn/5305-01-370-1138>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.511 inches and 0.625 inches

**Fastener Length:**

Between 0.594 inches and 0.625 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.226 inches and 0.243 inches

**Width Between Flats:**

Between 0.551 inches and 0.562 inches

**Hole Diameter:**

Between 0.060 inches and 0.068 inches

**End Application:**

Spec item

**Thread Diameter:**

0.375 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

70000 pounds per square inch

**Hardness Rating:**

235.0 brinell b

**Minimum Yield Strength:**

40000 pounds per square inch

**Hole Configuration Style:**

Hexagon flats

**Material:**

Steel comp 410 or steel comp 430 or steel comp 416

**Material Specification:**

Fed standard 66 federal standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0