## NSN 5305-01-370-6956

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-370-6956

The state of the s
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.500 inches
Fastener Length:
2.000 inches
Head Style:
Flat chamfer
Head Diameter:
0.425 inches
Head Height:
0.210 inches
Shoulder Diameter:
0.3070 inches first shoulder and 0.3080 inches first shoulder
Shoulder Length:
1.500 inches first shoulder
Internal Drive Style:
Torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
Shoulder Shape:
Round first shoulder
Material:
Aluminum alloy 7075
Material Specification:
Qq-a-200/11 federal specification single material response or qq-a-225/9 federal specification single material response or qq-a-250/12
federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 ty2 la1 military specification single treatment response or mil-a-8625 ty1 cl1 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## NSN 5305-01-370-6956

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-a-8625 spec.