NSN 5305-01-370-6956

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-370-6956

| The state of the s |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.500 inches |
| Fastener Length: |
| 2.000 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| 0.425 inches |
| Head Height: |
| 0.210 inches |
| Shoulder Diameter: |
| 0.3070 inches first shoulder and 0.3080 inches first shoulder |
| Shoulder Length: |
| 1.500 inches first shoulder |
| Internal Drive Style: |
| Torque |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Shoulder Shape: |
| Round first shoulder |
| Material: |
| Aluminum alloy 7075 |
| Material Specification: |
| Qq-a-200/11 federal specification single material response or qq-a-225/9 federal specification single material response or qq-a-250/12 |
| federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 ty2 la1 military specification single treatment response or mil-a-8625 ty1 cl1 military specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5305-01-370-6956

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-a-8625 spec.