NSN 5305-01-370-6957

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-370-6957

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.338 inches |
| Fastener Length: |
| Between 1.433 inches and 1.443 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.419 inches and 0.438 inches |
| Head Height: |
| Between 0.209 inches and 0.219 inches |
| Shoulder Diameter: |
| 0.308 inches first shoulder and 0.310 inches first shoulder |
| Shoulder Length: |
| 0.995 inches first shoulder and 1.005 inches first shoulder |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.250 inches |
| Width Across Flats: |
| 0.156 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Shoulder Shape: |
| Round first shoulder |
| Special Features: |
| 0.100 in wide undercut for thread relief, 0.182 in min dia, 0.193 in maximum dia |
| Color: |
| Black |
| Material: |
| Steel |
| Surface Treatment: |
| Oxide |
| Thread Series Designator: |
| Unrc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-370-6957

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

