## NSN 5305-01-370-9065

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-370-9065 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.060 inches and 0.070 inches **Fastener Length:** 0.1325 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.150 inches and 0.160 inches **Head Height:** Between 0.037 inches and 0.039 inches **First Diameter From Head:** Between 0.0756 inches and 0.0759 inches **Second Diameter From Head:** Between 0.047 inches and 0.052 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.554 inches and 0.556 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.0675 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.073 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-01-370-9065

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0