NSN 5305-01-370-9068

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-370-9068 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.745 inches and 0.755 inches **Head Style:** Fillister **Head Diameter:** Between 0.177 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **First Diameter From Head:** Between 0.085 inches and 0.090 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.495 inches and 0.505 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: 0.0937 inches Thready Qty Per Inch (tpi): 40 **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unrc Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-370-9068

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0