NSN 5305-01-370-9069

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-370-9069 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.620 inches and 0.630 inches **Head Style:** Fillister **Head Diameter:** Between 0.134 inches and 0.140 inches **Head Height:** Between 0.082 inches and 0.086 inches **First Diameter From Head:** Between 0.065 inches and 0.070 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.370 inches and 0.380 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: Between 0.077 inches and 0.078 inches Thready Qty Per Inch (tpi): 56 **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response and ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unrc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-370-9069

Externally Relieved Body Screw - Page 2 of 2



Demi			

No

Fiig:

A003b0