

View Online at <https://aerobasegroup.com/nsn/5305-01-370-9088>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.530 inches

Fastener Length:

Between 1.140 inches and 1.170 inches

Head Style:

Flat countersunk

Head Diameter:

0.328 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.3125 inches

Grip Length:

Between 0.615 inches and 0.635 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Countersink Angle:

Between 100.0 degrees and 101.0 degrees

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas672 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas2805 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.