NSN 5305-01-371-1771

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-371-1771

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.438 inches
Fastener Length:
Between 0.408 inches and 0.438 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.262 inches and 0.270 inches
Head Height:
Between 0.159 inches and 0.164 inches
Width Between Flats:
Between 0.1406 inches and 0.1426 inches
Internal Drive Style:
Err-090
Thread Diameter:
0.164 inches
Width Across Flats:
Between 0.1406 inches and 0.1426 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 33.0 rockwell c and 42.0 rockwell c
Screw Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Screw Material Specification:
Astm a493 assn standard all material responses
Screw Surface Treatment:
Cadmium
Screw Surface Treatment Specification:
Qq-p-416 type 1 cl 2 federal specification single treatment response
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-371-1771

Machine Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A500d0