NSN 5305-01-371-1771

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-371-1771

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.438 inches |
| Fastener Length: |
| Between 0.408 inches and 0.438 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.262 inches and 0.270 inches |
| Head Height: |
| Between 0.159 inches and 0.164 inches |
| Width Between Flats: |
| Between 0.1406 inches and 0.1426 inches |
| Internal Drive Style: |
| Err-090 |
| Thread Diameter: |
| 0.164 inches |
| Width Across Flats: |
| Between 0.1406 inches and 0.1426 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| Between 33.0 rockwell c and 42.0 rockwell c |
| Screw Material: |
| Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 |
| Screw Material Specification: |
| Astm a493 assn standard all material responses |
| Screw Surface Treatment: |
| Cadmium |
| Screw Surface Treatment Specification: |
| Qq-p-416 type 1 cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unrc |
| Specification Data: |
| 80205-nas1352 professional/industrial association standard |
| Shelf Life: |

N/a

NSN 5305-01-371-1771

Machine Screw - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A500d0