

View Online at <https://aerobasegroup.com/nsn/5305-01-371-3102>

Thread Direction:

Right-hand

Thread Length:

Between 9.0 millimeters and 10.0 millimeters

Fastener Length:

Between 9.5 millimeters and 10.0 millimeters

Head Style:

Flat countersunk undercut

Head Diameter:

5.5 millimeters

Head Height:

1.8 millimeters

Locking Feature:

Patch threads

Internal Drive Style:

Cross recess type 1

Thread Diameter:

3.0 millimeters

Thread Pitch In Millimeters:

0.5

External Thread Tolerance Class:

6g

Countersink Angle:

Between 90.0 degrees and 92.0 degrees

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

M

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0