

View Online at <https://aerobasegroup.com/nsn/5305-01-371-5142>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.403 inches

Fastener Length:

Between 1.138 inches and 1.168 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.4640 inches and 0.5066 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.250 inches

Grip Length:

Between 0.740 inches and 0.760 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.037 inches first hole

Special Features:

Torq-set recess per ms33781

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1580 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0