## NSN 5305-01-371-7233

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-371-7233 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.384 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.340 inches and 0.385 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 60000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1132 **Screw Material Specification:** Astm a29-79 assn standard all material responses **Screw Surface Treatment:** Zinc and chromate **Screw Surface Treatment Specification:** Astm b633-78 type 2 assn standard all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No Fiig:

**Demilitarization:** 

A500d0