NSN 5305-01-372-0341

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-372-0341 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.1563 inches and 0.2187 inches **Fastener Length:** Between 0.2843 inches and 0.3437 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.281 inches and 0.343 inches **Head Height:** Between 0.125 inches and 0.187 inches **Shoulder Diameter:** 0.1860 inches first shoulder and 0.1870 inches first shoulder **Shoulder Length:** 0.125 inches first shoulder and 0.128 inches first shoulder **Internal Drive Style:** Torque **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder Material: Steel comp 304 or steel comp xm-7 **Material Specification:** Astm a493 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 ty1 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-372-0341

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-21472 spec.