

View Online at <https://aerobasegroup.com/nsn/5305-01-372-0342>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.182 inches and 0.192 inches

Fastener Length:

Between 0.609 inches and 0.619 inches

Head Style:

Flat chamfer

Head Diameter:

0.451 inches

Head Height:

0.520 inches

Internal Drive Style:

Slot

Material Accommodated Thickness:

Between 0.032 inches and 0.093 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Material:

Aluminum alloy 6061 headsteel secondary washersteel comp 301 primary washersteel comp 302 springaluminum alloy 6061 stand-offsteel comp 301 fastener or steel comp 302 fastener or steel comp 302b fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304l fastener or steel comp 305 fastener or steel comp 308 fastener or steel comp 309 fastener or steel comp 309s fastener or steel comp 310 fastener or steel comp 310s fastener or steel comp 314 fastener or steel comp 316 fastener or steel comp 316l fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 348 fastener or steel comp 384 fastener or steel comp 385 fastener

Material Specification:

Qq-a-225/8 federal specification single material response headmil-s-5059 military specification single material response primary washerqq-w-423, cond b federal specification single material response springqq-a-225/8 federal specification single material response stand-off

Surface Treatment:

Anodize headpassivate secondary washerpassivate primary washerpassivate springanodize stand-offpassivate fastener

Surface Treatment Specification:

Mil-a-8625, ty1, cl1 military specification single treatment response headqq-p-35 federal specification single treatment response secondary washerqq-p-35 federal specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-a-8625, ty1, cl1 military specification single treatment response stand-offqq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure: