## NSN 5305-01-372-4717



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-372-4717 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.558 inches and 0.641 inches **Fastener Length:** Between 1.043 inches and 1.073 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.692 inches and 0.763 inches **Shoulder Diameter:** 0.405 inches first shoulder and 0.406 inches first shoulder **Shoulder Length:** 0.480 inches first shoulder and 0.510 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Mil-c-83499, type 2, class 3 military specification all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-01-372-4717

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83499 spec.