

View Online at <https://aerobasegroup.com/nsn/5305-01-372-6634>

Thread Direction:

Right-hand

Thread Length:

4.2 millimeters

Fastener Length:

Between 5.5 millimeters and 6.0 millimeters

Head Style:

Flat countersunk

Head Diameter:

Between 3.8 millimeters and 7.6 millimeters

Internal Drive Style:

Cross recess type 1

Thread Diameter:

3.0 millimeters

Min. Tensile Strength (psi):

80000 pounds per square inch

Thread Pitch In Millimeters:

0.5

External Thread Tolerance Class:

6g

Countersink Angle:

Between 90.0 degrees and 92.0 degrees

Screw Material:

Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347

Screw Material Specification:

Qq-s-763 federal specification all material responses or fed-std66 federal standard all material responses

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924 cl 4 military specification single treatment response

Color:

Black

Thread Series Designator:

M

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.