

View Online at <https://aerobasegroup.com/nsn/5305-01-373-0220>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.360 inches and 0.390 inches

Fastener Length:

Between 1.300 inches and 1.330 inches

Head Style:

Fillister

Head Diameter:

Between 0.557 inches and 0.577 inches

Head Height:

Between 0.235 inches and 0.265 inches

First Diameter From Head:

Between 0.170 inches and 0.180 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.910 inches and 0.970 inches

Point Style:

Cone

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Externally Relieved Body Diameter Quantity:

1

Product Name:

Navy special project

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.