## NSN 5305-01-373-0578

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-373-0578 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.433 inches **Fastener Length:** Between 0.480 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.195 inches and 0.225 inches **Locking Feature:** Patch **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 **Locking Feature Material:** Plastic polyamide **Screw Material Specification:** Qq-s-763 federal specification all material responses or fed-std66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5305-01-373-0578

Machine Screw - Page 2 of 2



Fiig:

A500d0