## NSN 5305-01-373-1552

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-373-1552 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.636 inches and 0.750 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.270 inches and 0.272 inches **Head Height:** Between 0.122 inches and 0.133 inches **Locking Feature:** Patch **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Locking Feature Material:** Plastic polyamide **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-373-1552

Machine Screw - Page 2 of 2



Fiig:

A500d0