NSN 5305-01-373-2599

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-373-2599

Thread Class:

Thread Class: За **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.313 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 **Material Specification:** Astm a493 assn standard all material responses **Surface Treatment:** Passivate and oxide **Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response and mil-c-13924 cl 4 military specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-373-2599

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.