

View Online at <https://aerobasegroup.com/nsn/5305-01-373-4839>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.641 inches

Fastener Length:

Between 1.259 inches and 1.306 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.692 inches and 0.763 inches

Head Height:

Between 0.1147 inches and 0.1167 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Single Shear Strength:

125000 pounds per square inch

Internal Drive Style:

High-torque

Thread Diameter:

0.375 inches

Grip Length:

Between 0.624 inches and 0.644 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

24

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Steel comp xm-13 fastener

Material Specification:

Ams 5629 assn standard single material response fastener

Surface Treatment:

Aluminum fastener and chromate fastener

Surface Treatment Specification:

Mil-c-83488 type 2 cl 3 military specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.