

View Online at <https://aerobasegroup.com/nsn/5305-01-373-4839>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.641 inches

**Fastener Length:**

Between 1.259 inches and 1.306 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.692 inches and 0.763 inches

**Head Height:**

Between 0.1147 inches and 0.1167 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Single Shear Strength:**

125000 pounds per square inch

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.624 inches and 0.644 inches

**Features Provided:**

Cetyl alcohol lubricant

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

**Material:**

Steel comp xm-13 fastener

**Material Specification:**

Ams 5629 assn standard single material response fastener

**Surface Treatment:**

Aluminum fastener and chromate fastener

**Surface Treatment Specification:**

Mil-c-83488 type 2 cl 3 military specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.