## NSN 5305-01-374-0388

Demilitarization:

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-374-0388
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.437 inches
Fastener Length:
0.437 inches
Head Style:
Knurled no. 1
Head Diameter:
0.451 inches
Head Height:
0.520 inches
Internal Drive Style:
Cross recess type ii
Material Accommodated Thickness:
Between 0.031 inches and 0.062 inches
Thread Diameter:
0.190 inches
Features Provided:
Sleeve
Thready Qty Per Inch (tpi):
32
Color:
Black headblack fastener
Material:
Aluminum alloy 6061 headsteel comp 302 springaluminum alloy 6061 stand-offsteel comp 302 fastener or steel comp 304 fastener or steel
comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener
Material Specification:
Qq-a-225/8 federal specification single material response headqq-w-423 comp fs302, cond b federal specification single material response
springqq-a-225/8 federal specification single material response stand-offastm a493 federal specification all material responses fastener
Surface Treatment:
Anodize headpassivate springanodize stand-offoxide fastener
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response headqq-p-35 federal specification single treatment response springmil-a-8625
military specification single treatment response stand-offmil-c-13924 military specification single treatment response fastener
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-374-0388

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-a-8625 spec.