## NSN 5305-01-374-3272

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-374-3272 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 1.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **First Diameter From Head:** 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.500 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 or steel comp 384 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

Unc

**Thread Series Designator:** 

## NSN 5305-01-374-3272

Externally Relieved Body Screw - Page 2 of 2



| Specification Or Standard: |
|----------------------------|
| 6 type                     |
| Shelf Life:                |
| N/a                        |
| Unit Of Measure:           |
|                            |
| Demilitarization:          |
| No                         |

Fiig: A003b0