

View Online at <https://aerobasegroup.com/nsn/5305-01-374-3459>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.095 inches and 0.105 inches

Fastener Length:

Between 0.270 inches and 0.280 inches

Head Style:

Hexagon

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.181 inches and 0.187 inches

Internal Drive Style:

Slot

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

40

Product Name:

Navy special project

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 301 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924, cl4 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.