

View Online at <https://aerobasegroup.com/nsn/5305-01-374-4484>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.188 inches and 0.218 inches

**Fastener Length:**

Between 1.235 inches and 1.265 inches

**Head Style:**

Knurled no. 2

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**Internal Drive Style:**

Cross recess type 1

**Material Accommodated Thickness:**

Between 0.064 inches and 0.125 inches

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Material:**

Steel comp 301 secondary washersteel comp 302 springsteel comp 304 stand-offsteel fastener

**Material Specification:**

Mil-s-5059 military specification single material response secondary washerfed standard 66 federal standard all material responses primary washerqq-w-423 federal specification single material response springst0304 federal standard single material response stand-offfed standard 66 federal standard all material responses fastener

**Surface Treatment:**

Oxide secondary washeroxide primary washerpassivate springoxide stand-offoxide fastener

**Surface Treatment Specification:**

Mil-c-13924, cl2 military specification single treatment response secondary washermil-c-13924, cl2 military specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-c-13924, cl2 military specification single treatment response stand-offmil-c-13924, cl2 military specification single treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**