

View Online at <https://aerobasegroup.com/nsn/5305-01-374-5393>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.235 inches and 0.280 inches

Fastener Length:

Between 1.110 inches and 1.140 inches

Head Style:

Pan

Head Diameter:

Between 0.186 inches and 0.199 inches

Head Height:

Between 0.100 inches and 0.124 inches

Internal Drive Style:

Cross recess type 1

Material Accommodated Thickness:

Between 0.086 inches and 0.106 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Material:

Steel comp 301 secondary washersteel comp 302 primary washersteel comp 302 springsteel comp 304 stand-offsteel comp 302 fastener

Material Specification:

Mil-s-5059 military specification single material response secondary washerastm a 493 assn standard single material response primary washerams 5688 assn standard single material response springqq-s-763 federal specification single material response stand-offastm a 493 assn standard single material response fastener

Surface Treatment:

Oxide secondary washeroxide primary washerpassivate springoxide stand-offoxide fastener

Surface Treatment Specification:

Mil-c-13924 military specification single treatment response secondary washermil-c-13924 military specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-c-13924 military specification single treatment response stand-offmil-c-13924 military specification single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):