## NSN 5305-01-374-5393

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-374-5393 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.235 inches and 0.280 inches **Fastener Length:** Between 1.110 inches and 1.140 inches **Head Style:** Pan **Head Diameter:** Between 0.186 inches and 0.199 inches **Head Height:** Between 0.100 inches and 0.124 inches **Internal Drive Style:** Cross recess type 1 **Material Accommodated Thickness:** Between 0.086 inches and 0.106 inches **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 301 secondary washersteel comp 302 primary washersteel comp 302 springsteel comp 304 stand-offsteel comp 302 fastener **Material Specification:** Mil-s-5059 military specification single material response secondary washerastm a 493 assn standard single material response primary washerams 5688 assn standard single material response springqq-s-763 federal specification single material response stand-offastm a 493 assn standard single material response fastener **Surface Treatment:** Oxide secondary washeroxide primary washerpassivate springoxide stand-offoxide fastener **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response secondary washermil-c-13924 military specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-c-13924 military specification single treatment response stand-offmil-c-13924 military specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

Fiig:

A003b0