

View Online at <https://aerobasegroup.com/nsn/5305-01-374-5614>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.500 inches

**Fastener Length:**

Between 0.470 inches and 0.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.105 inches and 0.120 inches

**Width Between Flats:**

Between 0.305 inches and 0.312 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Screw Material:**

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022

**Screw Material Specification:**

Qq-s-637 federal specification all material responses or fed-std66 federal standard all material responses

**Screw Surface Treatment:**

Zinc and chromate

**Screw Surface Treatment Specification:**

Astm b633 type 2 cl 3 assn standard all treatment responses

**Color:**

Bronze or olive drab

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0