NSN 5305-01-374-5946

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-374-5946 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.516 inches **Fastener Length:** Between 1.001 inches and 1.031 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.515 inches and 0.566 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-374-5946

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0