## NSN 5305-01-374-6947

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-374-6947 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 2.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 1.000 inches and 1.022 inches **Grip Diameter:** Between 0.4950 inches and 0.4990 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.485 inches and 1.515 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4130 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-6758 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas517 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-01-374-6947

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.