NSN 5305-01-374-7647

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-374-7647 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.625 inches **Fastener Length:** 1.750 inches **Head Style:** Fillister **Head Diameter:** 0.562 inches **Head Height:** 0.380 inches **First Diameter From Head:** Between 0.260 inches and 0.270 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.125 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel **Surface Treatment:** Cadmium and chromate or zinc and chromate or zinc or aluminum and chromate **Surface Treatment Specification:** Q-p-416, ty2, cl2 federal specification 1st treatment response or mil-c-87115, cl1, ty1 military specification 2nd treatment response or astm-8633, ty2, sc1 assn standard 3rd treatment response or mil-c-83488, ty2, cl3 military specification 4th treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A003b0

No

NSN 5305-01-374-7647

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-87115 spec.