
Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-374-7650

view Online at https://delobasegroup.com/hsi//ocos of or 4 / oco
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.500 inches
Fastener Length:
Between 0.469 inches and 0.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.1875 inches and 0.1900 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Special Features:
Surface treatment 0.0003 in. Thick, chromate treatment: bronze or olive drab
Color:
Bronze or olive drab
Material:
Steel uns k03104
Material Specification:
Astm a574 assn standard single material response
Surface Treatment:
Zinc or chromate
Surface Treatment Specification:
Astm b633 type 2 assn standard all treatment responses
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-374-7650

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

