## NSN 5305-01-374-7651

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-374-7651 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **End Application:** Mrap - m-atv with cs13 pop and sne **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Special Features:** Surface treatment 0.0003 in. Thick, chromate treatment: bronze or olive drab Color: Bronze or olive drab Material: Steel uns k03104 **Material Specification:** Astm a574 assn standard single material response **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Astm b633 type 2 assn standard all treatment responses **Thread Series Designator:** Unc

Shelf Life:

N/a

## NSN 5305-01-374-7651

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0