NSN 5305-01-374-7653

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-374-7653

Thread Class:
3a Three d Direction
Thread Direction:
Right-hand
Thread Length:
0.375 inches
Fastener Length:
Between 0.922 inches and 0.952 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.625 inches and 0.635 inches
Grip Diameter:
Between 0.3106 inches and 0.3112 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.312 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.818 inches first hole
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4967 assn standard single material response
Thread Series Designator:
Unjf Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-374-7653

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

