## NSN 5305-01-374-8349

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-374-8349 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Locking Feature:** Pellet locking feature **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 30000 pounds per square inch Material: Plastic polyamide locking featuresteel comp 303 fastener or steel comp 316 fastener or steel comp 304 fastener or steel comp 305 fastener **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unc **Specification Data:** 80205-nas1352 professional/industrial association standard

N/a

**Unit Of Measure:** 

Shelf Life:

## NSN 5305-01-374-8349

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0