

View Online at <https://aerobasegroup.com/nsn/5305-01-374-8359>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.235 inches and 0.280 inches

**Fastener Length:**

Between 1.047 inches and 1.077 inches

**Head Style:**

Knurled no. 3

**Head Diameter:**

Between 0.299 inches and 0.329 inches

**Head Height:**

Between 0.100 inches and 0.130 inches

**Internal Drive Style:**

Cross recess type 1

**Material Accommodated Thickness:**

Between 0.146 inches and 0.166 inches

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Color:**

Black secondary washerblack primary washerblack stand-offblack fastener

**Material:**

Steel comp 301 secondary washersteel comp 302 primary washersteel comp 302 springsteel comp 304 stand-offsteel comp 302 fastener

**Material Specification:**

Mil-s-5059 military specification single material response secondary washerastm a 493 assn standard single material response primary washerams 5688 assn standard single material response springqq-s-763 federal specification single material response stand-offastm a 493 assn standard single material response fastener

**Surface Treatment:**

Oxide secondary washeroxide primary washerpassivate springoxide stand-offoxide fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.