## NSN 5305-01-374-9234

Panel Screw Assembly - Page 1 of 1

Fiig: A003b0



View Online at https://aerobasegroup.com/nsn/5305-01-374-9234 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** 1.362 inches **Head Style:** Fillister **Internal Drive Style:** Cross recess type ii **Material Accommodated Thickness:** Between 0.245 inches and 0.255 inches **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Steel comp 302 secondary washersteel comp 302 primary washer or steel comp 303 primary washer or steel comp 304 primary washer or steel comp 305 primary washer or steel comp 316 primary washersteel comp 302 springsteel comp 302 stand-off or steel comp 303 stand-off or steel comp 304 stand-off or steel comp 305 stand-off or steel comp 316 stand-offiron alloy 660 fastener **Material Specification:** Ams 5737 assn standard single material response fastener **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No