

View Online at <https://aerobasegroup.com/nsn/5305-01-375-2387>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.656 inches

**Fastener Length:**

Between 2.452 inches and 2.499 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.880 inches and 0.890 inches

**Head Height:**

0.188 inches

**Grip Diameter:**

Between 0.4358 inches and 0.4367 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.4375 inches

**Grip Length:**

1.812 inches

**Width Across Flats:**

Between 0.3135 inches and 0.3165 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, ty ii, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas337a23 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.