

View Online at <https://aerobasegroup.com/nsn/5305-01-375-2387>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.656 inches

Fastener Length:

Between 2.452 inches and 2.499 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.880 inches and 0.890 inches

Head Height:

0.188 inches

Grip Diameter:

Between 0.4358 inches and 0.4367 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.4375 inches

Grip Length:

1.812 inches

Width Across Flats:

Between 0.3135 inches and 0.3165 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140

Material Specification:

Mil-s-5626 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas337a23 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.