## NSN 5305-01-375-7350

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-375-7350

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.750 inches
Fastener Length:
Between 1.210 inches and 1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.176 inches and 0.183 inches
Head Height:
Between 0.108 inches and 0.112 inches
Width Between Flats:
Between 0.0937 inches and 0.0952 inches
Internal Drive Style:
Err-090
Thread Diameter:
0.112 inches
Width Across Flats:
Between 0.0937 inches and 0.0952 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5731 assn standard single material response or ms 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-375-7350

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0