NSN 5305-01-376-0746

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-376-0746 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.501 inches **Fastener Length:** 0.939 inches **Head Style:** Pan **Head Diameter:** Between 0.597 inches and 0.612 inches **Head Height:** Between 0.176 inches and 0.183 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Surface Finish:** 32.0 microinches threads Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-376-0746

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0